

Arizona Tools Company, Kolkata INDIA  
Cell: +91 98300 30618, 90380 81456 Email: info@aztc.in

# TLS-OWC Preset Torque Screwdrivers

The TLS-OWC torque screwdriver is a one-way clutch system is designed for the screwdriver to apply torque in one direction and lockup in the opposite direction for easy screw removal. Ideal for maintenance and refurbishing applications.





CHOOSE THE  
MODEL  
BELOW FOR  
PURCHASING  
DETAILS

Model	Item Name / Number	Handle Color	American	S.I.	Metric	Drive Size
Standard (OWC)	020293	Green	4.4 - 36 lbf.in	50 - 406 cN.m	5.1 - 41 kgf.cm	1/4" F/Hex
Standard (OWC)	020302	Blue	4.4 - 36 lbf.in	50 - 406 cN.m	5.1 - 41 kgf.cm	1/4" F/Hex
Standard (OWC)	020304	Gold	4.4 - 36 lbf.in	50 - 406 cN.m	5.1 - 41 kgf.cm	1/4" F/Hex
Minor (OWC)	020298	Blue	1.2 - 12 lbf.in	14 - 135 cN.m	1.4 - 13.7 kgf.cm	1/4" F/Hex
TLS1360 (OWC)	020290	Black	22 - 120 lbf.in	2.5 - 13.6 N.m	25.3 - 138 kgf.cm	1/4" F/Hex
Minimaster (OWC)	020289	Gold	5.7 - 32 ozf.in	4 - 22 cN.m	0.4 - 2.2 kgf.cm	1/4" F/Hex
Minor (OWC)	020299	Green	1.2 - 12 lbf.in	14 - 135 cN.m	1.4 - 13.7 kgf.cm	1/4" F/Hex
Minor (OWC)	020300	Red	1.2 - 12 lbf.in	14 - 135 cN.m	1.4 - 13.7 kgf.cm	1/4" F/Hex
Minor (OWC)	020301	Gold	1.2 - 12 lbf.in	14 - 135 cN.m	1.4 - 13.7 kgf.cm	1/4" F/Hex

## Tools Benefits

- Various models that range from 5.7 ozf.in - 120 lbf.in. Ideal for maintenance and refurbishing applications. Screwdriver torques in the CW direction only. Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer. Four different colored lightweight aluminum handles allow color coding of specific torque values in production areas. (TLS1360 - Black only)
- **The preferred and certified ranges of these tools is in accordance with the requirements of ISO 6789 (+/- 6% of indicated setting).**