

SlimGrip Tongs



*Suitable for use
in any position*

- » Designed to work connections with narrow gripping areas
- » Self-adjusting, ratcheting "pipe wrench" with a torque rating
- » Can easily be placed either on top of or underneath the workpiece
- » Sizes capable of delivering up to 7,500 ft.-lbs. torque

Specifications

Part No.	O.D.	Gripping Width	Handle Length	Weight
SLG10	1" - 2"	1.19"	16"	9 lbs.
SLG13	2-3/8" - 4"	1.75"	28"	44-1/2 lbs.
SLG15	3-3/4" - 6-1/2"	1.25"	33"	65 lbs.

>>> Maximum Working Loads <<<

*Torques vary according to tong being used.
See Torque Table on product page of website.*



WARNING! Do Not Exceed Maximum Working Load! Overloading may result in SERIOUS INJURY or DEATH!
Always use a load cell or other calibrated indicating device to monitor the line pull on the tong to avoid overload.
Do not operate without a manual. Follow OSHA, NSC, etc. standards, safe practices, and procedures.



Rig Wrench



- » For fast makeup or breakout of drill pipe on water well and blast hole rigs
- » Self-adjusting, non-jamming ratchet action
- » Easily applied or removed from the workpiece
- » Capable of delivering up to 16,000 ft.-lbs. torque

Specifications

Part No.	O.D.*	Gripping Width	Torque Arm Length	Weight
PRWA01	3-1/2" - 5"	2.25"	approx. 18"***	53 lbs.
PRWA01-D	3-1/2" - 5"	2.25"	approx. 22"***	55 lbs.

*T-4 or T-7 Inserts must be used to work used to work 3-1/2" O.D.

Diamond Point or Teeth Inserts can be used to work all other O.D.s

**Torque Arm Length will vary from 17.38" to 19.38" depending on O.D. being worked

***Torque Arm Length will vary from 21.25" to 22.63" depending on O.D. being worked

>>> Maximum Working Loads <<<

*Torques vary according to tong being used.
See Torque Table on product page of website.*



WARNING! Do Not Exceed Maximum Working Load! Overloading may result in SERIOUS INJURY or DEATH!
Always use a load cell or other calibrated indicating device to monitor the line pull on the tong to avoid overload.
Follow OSHA, NSC, etc. standards, safe practices, and procedures.

