

## Striking Wrench

### 6-pt. Straight



- » I-beam design for greater handle strength
- » Clearance in overall head diameter when working flange connections
- » Large striking surface
- » Forged from alloy steel and heat-treated for strength and maximum tool life



WEAR EYE PROTECTION



#### Specifications

Part No.	Stud Size	Nut Size	Head Diameter	Weight
SW01	5/8"	1-1/16"	1-11/16"	1-7/8 lbs.
SW02	3/4"	1-1/4"	1-15/16"	2 lbs.
SW03	7/8"	1-7/16"	2-1/4"	3-1/4 lbs.
SW04	1"	1-5/8"	2-1/2"	4-5/8 lbs.
SW05	1-1/8"	1-13/16"	2-11/16"	4-3/4 lbs.
SW06	1-1/4"	2"	2-15/16"	5-5/8 lbs.
SW07	1-3/8"	2-3/16"	3-3/16"	6-7/8 lbs.
SW08	1-1/2"	2-3/8"	3-7/16"	7-5/8 lbs.
SW09	1-5/8"	2-9/16"	3-11/16"	8-1/2 lbs.
SW10	1-3/4"	2-3/4"	3-7/8"	8-3/4 lbs.
SW11	1-7/8"	2-15/16"	4-1/4"	9-7/8 lbs.
SW12	2"	3-1/8"	4-3/8"	10-1/4 lbs.
SW13	2-1/4"	3-1/2"	4-7/8"	11-3/8 lbs.
SW14	2-1/2"	3-7/8"	5-1/4"	13-1/4 lbs.

## Striking Face Box Wrench

### 12-pt. Offset



- » Drop-forged alloy steel
- » Surface coated for rust protection
- » 45° offset head with a 12-point opening



WEAR EYE PROTECTION



#### Specifications

Part No.	Opening / Nut Size	Length	Weight
SWT20	1-1/16"	10-1/2"	2-1/4 lbs.
SWT21	1-1/8"	10-1/2"	2-1/4 lbs.
SWT22	1-1/4"	11"	2-3/4 lbs.
SWT23	1-5/16"	11"	2-3/4 lbs.
SWT24	1-7/16"	11-3/4"	3-3/8 lbs.
SWT25	1-1/2"	11-3/4"	3-1/4 lbs.
SWT26	1-5/8"	12"	4 lbs.
SWT27	1-11/16"	12"	4 lbs.
SWT28	1-3/4"	12-1/2"	5-7/8 lbs.
SWT29	1-13/16"	12-1/2"	5-7/8 lbs.
SWT30	1-7/8"	12-1/2"	5-3/4 lbs.
SWT31	1-15/16"	13-1/4"	6-3/4 lbs.
SWT32	2"	13-1/4"	6-1/2 lbs.
SWT33	2-1/8"	13-1/2"	6-3/4 lbs.
SWT34	2-3/16"	13-1/2"	6-5/8 lbs.
SWT35	2-1/4"	13-1/2"	6-5/8 lbs.
SWT36	2-5/16"	14"	9-1/8 lbs.
SWT37	2-3/8"	14"	9 lbs.
SWT38	2-1/2"	14-3/4"	9-1/4 lbs.
SWT39	2-9/16"	14-3/4"	9-1/4 lbs.
SWT40	2-5/8"	14-3/4"	9-1/8 lbs.
SWT41	2-3/4"	16"	13 lbs.
SWT42	2-7/8"	16"	12-5/8 lbs.
SWT43	2-15/16"	16"	12-3/4 lbs.
SWT44	3"	16-1/2"	15-1/4 lbs.
SWT45	3-1/8"	16-1/2"	15-1/8 lbs.