NOTE: The image of Striking Box Wrench in our catalog is 12 point.



- 報造,扭力加强。 One-time die-forged,strong torque.
 采用德国DIN7444标准。

米市被国DIN1444所定。 In accordance to DIN7444 standard.
 圆弧内角设计,有效保护螺母及扳手延长使用寿命。

Arc point design, effectively secure and extend service life of nuts and wrench.

货号 特种钢制	规格		🔳 🖬 (g)
	Size(mm)	L(mm)	特种钢制
CT3310-17	17	145	200
CT3310-19	19	145	200
CT3310-22	22	155	230
CT3310-24	24	165	250
CT3310-27	27	175	310
CT3310-30	30	185	405
CT3310-32	32	185	430
CT3310-36	36	205	520
CT3310-41	41	225	710
CT3310-46	46	235	900
CT3310-50	50	250	1050
CT3310-55	55	265	1360
CT3310-60	60	274	1500
CT3310-65	65	298	2100
CT3310-70	70	320	2350
CT3310-75	75	326	2850
CT3310-80	80	350	3400
CT3310-85	85	355	4100
CT3310-90	90	380	5200
CT3310-100	100	410	6700
CT3310-110	110	445	8640
CT3310-120	120	480	10400
CT3310-130	130	520	11900
CT3310-140	140	520	12280
CT3310-150	150	565	13650
CT3310-160	160	585	15800

Wrench, Striking Open



- •采用德国DIN133标准。
- In accordance to DIN 133 standard. 锻造,扭力加强。

One-time die-forged,strong torque. • 表面喷黑处理,环保美观,防锈性强。 Black-spray on surface, beautiful and environmental, high anti-rust.

货号 特种钢制	规格		正司(g)
	Size (mm)	L(mm)	特种钢制
CT3304-22	22	135	190
CT3304-24	24	150	230
CT3304-27	27	175	350
CT3304-30	30	190	500
CT3304-32	32	190	600
CT3304-36	36	210	700
CT3304-38	38	220	820
CT3304-41	41	230	900
CT3304-46	46	250	1200
CT3304-50	50	275	1500
CT3304-55	55	305	2000
CT3304-60	60	315	2200
CT3304-65	65	335	3100
CT3304-70	70	370	4000
CT3304-75	75	375	4500
CT3304-80	80	400	5500
CT3304-85	85	400	5500
CT3304-90	90	445	8000
CT3304-100	100	485	11500
CT3304-110	110	512	14000
CT3304-120	120	530	16300
CT3304-130	130	560	18500
CT3304-140	140	630	24000
CT3304-150	150	630	24000