

1000V INSULATED TORQUE WRENCHES



EGA Master insulated tools comply with IEC 60900 international standard, each one of the pieces being tested at 10,000V (10 times the voltage we certify). They are also tested rigorously according to what the norms establishes: adherence test, impact test, flame propagation test and dielectric penetration test.



MAIN APPLICATION FIELDS

Electrical installation	High Voltage networks	Fire-fighters	Automotive
Power Plants	Low Voltage networks	Lighting installation and repair	Railway industry
Electric Stations and substations	Telecommunications	Aeronautical	Electrical component maintenance

CAUTION

- 1 Don't ever use tools under voltage if they present pores, fissures, encrusted elements or if the white insulation layer is visible.
- 2 **Insulating floors and safety shoes** are recommended to work under voltage.
- 3 **Avoid contact with water** while working under voltage.
- 4 **Do not ever touch directly any item that may be under voltage.** Use a voltage tester to check first.

1000V INSULATED TORQUE WRENCHES

EGA Master 1000V torque Wrenches are the perfect tools for controlled tightening thanks to their precision, endurance and variety.

They are particularly suitable for high voltage work and electrical assembly applications.



 **1.000V**
IEC 60900

1 +4% accuracy.

2 Anti-slippery handle.

3 Individual box.

1000V INSULATED TORQUE WRENCHES



COD.		N.m	Accuracy CW (clockwise)	L (mm)		
79990	1/4	5-25	+4%	290	0,6	1
79995	3/8					
79993		10-50				
79991		20-100		390	0,7	
79992	1/2	40-200		550	1,7	
79994						

 **1000V** | IEC 60900 | 12M

TECHNICAL SPECIFICATIONS

MATERIAL	Torque wrench	Steel
	Insulation	TPU, TPE and ABS
HARDNESS	Square drive	46-52 HRc
FINISH	RAL 2009 orange color and black color	
TEETH	36	

12M 12 MONTHS OF WARRANTY

1000V INSULATED TORQUE WRENCHES



**Reversible
tightening**

COD.	AF inch	N.m	Lb.ft	Accuracy CW (clockwise)	L (mm)	Kg	
79434	3/8	20-100	14,7-73,6	+4%	405	1,3	1

12M **1000V** | IEC 60900 | 12M

TECHNICAL SPECIFICATIONS

MATERIAL	Torque wrench	Steel
	Insulation	ABS
HARDNESS	Square drive	46-52 HRC
FINISH	RAL 2009 orange color and black color	
TEETH	72	



COD.	AF inch	N.m	Lb.ft	Accuracy CW (clockwise)	L (mm)	Kg	
79435	1/2"	20-200	15-150	+4%	500	1,4	1

12M **1000V** | IEC 60900

TECHNICAL SPECIFICATIONS

MATERIAL	Torque wrench	Steel
	Insulation	PP+TPR
HARDNESS	Square drive	46-52 HRC
FINISH	RAL 2009 orange color and black color	
TEETH	72	

1000V INSULATED PRESET TORQUE WRENCHES



COD.	AF inch	N.m	Accuracy CW (clockwise)	L (mm)	Kg	
30068	1/4	5-25	+4%	290	0,6	1
30069	1/2	10-50				
30070		20-100				
30071	3/8	10-50		290	0,6	
30072	1/2	40-200		565	1,7	
30073	3/8	5-25		290	0,6	

12M **1000V** | IEC 60900 | 12M

TECHNICAL SPECIFICATIONS

MATERIAL	Torque wrench	Steel
	Insulation	TPU, TPE and ABS
HARDNESS	Square drive	46-52 HRC
FINISH	RAL 2009 orange color and black color	
TEETH	36	

12M 12 MONTHS OF WARRANTY

This document has been created by and is the property of EGA Master S.L. Thus, all intellectual rights belong to EGA Master. Any total or partial copy of this document in any physical, electronic or any other form is strictly forbidden. EGA Master will legally proceed against any infringement of these rights.